

## Compact Optical Resin Dehumidifying Dryer

			NX-3	NX-5
Compatible molding machines	tf		--50	--80
Drying capacity (in the PC use)	kg/h		1.0	1.6
Max. working temperature	°C		150	150
Loading capacity	L(kg)		5 (3)	8 (5)
Compressed air	Air pressure	MPa	0.7	0.7
	Air consumption	NL/min	25	25
Power	Total electric capacity (50/60Hz)	kVA	3.78 / 3.92	3.78 / 3.92
	Power consumption (50/60Hz)	kW	2.23 / 2.53	2.23 / 2.53
	Heater power	kW	1.6	1.6
	Dryer blower power (50/60Hz)	kW	0.08	0.08
	Supply blower power (50/60Hz)	kW	0.55 / 0.85	0.55 / 0.85
	Power supply standard		200 / 220V 50 / 60Hz 3ø	
	Power plug		20A-3P plug with protective ground	
Dryer outer dimensions (WxDxH)	mm		340 x 685 x 1,429	340 x 685 x 1,429
Dryer drum outer dimensions (øxH)	mm		200 x 958	200 x 1,078
Dryer weight	kg		112	112
Dryer drum weight	kg		23	27
Accessories	N2 gas inlet		N2 gas connection port (with snap-on coupler) x1	
	Antistatic hose		ø25mm x 4m x 1	
	Suction hose		ø25mm x 4m x 1	
	Silicone duct hose		ø38mm x 2m x 2	
	Suction nozzle		ø25mm x 1	

- Dryer drum outer dimensions and weight include the standard ZH-04 hopper.
- Specifications are subject to change without notice.